Conforms to OSHA HazCom 2012 Standard

Section 1 - Identification

Product Identifier BULLDOZER II No Rinse No Scrub Liquifying Stripper

Recommended use Floor finish remover.

Recommended restrictions For commercial and industrial use only.

Manufacturer / Importer / Supplier / Distributor Information

Company Name Janilink

Address 3545 McCall Place, Ste. D, Doraville, GA 30340

Classification

Emergency Phone 888-234-2255

Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

	Classification	Category	
Physical Hazards	Not Classified		
Health Hazards	Acute toxicity, dermal	4	
	Acute toxicity, inhalation	4	
	Acute toxicity, oral	4	
	Serious eye damage/eye irritation	1	
	Skin corrosion/irritation	1	
	Specific target organ toxicity, single exposure	3	TARGET ORGAN: respiratory tract irritation

OSHA defined hazards

Label Elements Hazard Symbol Not Classified.



Signal Word Danger

Hazard statement Causes severe skin burns and eye damage. Harmful if swallowed, in contact with skin

or if inhaled. May cause respiratory irritation.

Precautionary statement

Prevention Do not breathe mist or vapor. Use only in well-ventilated areas. Wear protective

gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this

Category

product. Wash thoroughly after handling. Keep out of reach of children.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

Storage Store locked up. Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

Section 3 - Composition/Information on ingredients

Mixture

Hazardous Components

 Ingredient Name
 CAS #
 %

 2-Butoxyethanol
 111-76-2
 25 - 45

 2-Amino Ethanol
 141-43-5
 5 - 10

Section 4 - First-aid Measures

Inhalation Move to fresh air. If not breathing, give artificial respiration or give oxygen by trained

Conforms to OSHA HazCom 2012 Standard

personnel. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention immediately.

Skin contact Remove contaminated clothing and shoes. Immediately flush skin with plenty of water.

Get prompt medical attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting

the upper and lower eyelids. Check and remove contact lenses. Continue to rinse for

at least 10 minutes. Get medical attention immediately.

Ingestion Rinse mouth thoroughly with water. DO NOT induce vomiting. If victim is fully

conscious, give a cupful of water. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than the hips to help prevent aspiration.

Call a physician or poison control center immediately.

Most Important symptoms / effects, acute and delayed Indication of immediate medical attention and special treatment General Information Causes skin and eye burns. May cause respiratory tract irritation. Symptoms may be

delayed.

Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Immediate medical attention is required. In case of shortness of breath, give oxygen. Keep victim warm.

Section 5 - Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Specific hazards arising from the chemical Carbon dioxide, alcohol-resistant foam, dry chemical, water spray, or water fog.

Do not use water jet as an extinguisher, as this will spread the fire.

None known.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment. Self-contained breathing apparatus and full

protective clothing must be worn in case of fire.

Fire-fighting equipment /instruction Move containers from fire area if you can do it without risk. Use water spray to keep

fire-exposed containers cool.

Section 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures.

Isolate area. Keep unnecessary personnel away. Use personal protection as

recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up

Contain spill. Absorb spill with vermiculite or other inert material, then place in a

container for chemical waste. Flush area with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Section 7 - Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Do not breathe mist or vapor. Keep

container closed. Wash thoroughly after handling. Use Personal Protective Equipment

recommended in section 8 of the SDS.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials. Keep container closed. Keep out of reach of children.

Conforms to OSHA HazCom 2012 Standard

Section 8 - Exposure control/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Type Value

2-Amino Ethanol (CAS 141-43-5) TWA 6 mg/m³, 3 ppm 2-Butoxyethanol (CAS 111-76-2) TWA 240 mg/m³, 50 ppm

US. ACGIH Threshold Limit Values

Component Type Value
2-Butoxyethanol (CAS 111-76-2) TWA 20 ppm
2-Amino Ethanol (CAS 141-43-5) STEL 6 ppm
2-Amino Ethanol (CAS 141-43-5) TWA 3 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components Type Value

 2-Amino Ethanol (CAS 141-43-5)
 STEL
 15 mg/m³, 6 ppm

 2-Amino Ethanol (CAS 141-43-5)
 TWA
 8 mg/m³, 3 ppm

 2-Butoxyethanol (CAS 111-76-2)
 TWA
 24 mg/m³, 5 ppm

US. ACGIH. BEIs. Biological Exposure Indices

Component Value Determinate Specimen Sampling

2-Butoxyethanol (CAS 111-76-2) 200 mg/g Butoxyacetic acid Creatinine in urine

(BAA), with hydrolysis

Exposure guidelinesUse personal protective equipment as required. Keep working clothes separately.

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components Exposure

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed though the skin.

US.Minnesota Hazardous Substances List (Minn. Rules 5206.0400).

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US.NIOSH: Pocket Guide to Chemical Hazards

Component Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.100)

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.OSHA Table Z-1-A (29 CFR 1910.100)

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.Tennesee. OELs Occupational Exposure Limits, Table Z1A Components Exposure

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed though the skin.

Appropriate engineering controls Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection If use of product risks exposure to contact, wear safety glasses with side shields.

Skin protection

Hand protection Impervious gloves are recommended for prolonged use.

Other If use of product risk exposure to contact, wear suitable protective clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended

exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to

assure compliance with OSHA 29 CFR 1910.134.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

^{* -} For sampling details, please see the source document.

Conforms to OSHA HazCom 2012 Standard

Section 9 - Physical and chemical properties

Appearance Clear.

Physical state Liquid.

Form Liquid.

Color Pale Straw.

Odor Sassafras.

Odor threshold Not available.

pH 11.7

Melting point/freezing point Not available.

Initial boinging point and 212 °F (100 °C)

boiling range

Flash point >201°F (94°C) TCC
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available. Not available. Flammability limit - upper (%) Not available. **Explosive limit - lower (%)** Explosive limit - upper (%) Not available. Similar to water. Vapor pressure Vapor density Similar to water. Relative density 0.97 ± 0.01 75 °F (23.9 °C) Relative density temperature Solubilities (water) 100 % Soluble. Partition Coefficient n-Not available

octanol/water

Auto-ignition temperatureNot AvailableDecomposition temperatureNot AvailableViscosity< 10 cP</th>

Viscosity Temperature 75 °F (23.9 °C)

Conforms to OSHA HazCom 2012 Standard

Section 10 - Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possiblity of hazardous reactio Hazardous polymerization does not occur.

Conditions to Avoid Keep away from heat and direct sunlight. Contact with incompatible materials.

Incompatible materials Oxidizing agents.

Hazardous Decomposition Pro Carbon monoxide. Carbon dioxide. Nitrogen oxides.

Section 11 - Toxicological information

Information on likely routes of exposure

May cause burns of the gastrointestinal tract if swallowed. Ingestion

Irritating to respiratory system. May cause burns in mucous membranes, throat, Inhalation

esophagus and stomach.

Skin contact Causes skin burns.

Eve contact Causes serious eye damage.

Symptoms related to the physical,

chemical and toxicological

Causes skin and eye burns. May cause respiratory tract irritation. Symptoms may be delayed.

characteristics

Information on toxicological effects.

Harmful if inhaled, absorbed through skin, or swallowed. **Acute toxicity**

Code Species Results Components Level Type 2-Amino Ethanol (CAS 141-43-5) Acute Dermal LD50 Rabbit 1025 mg/kg Oral LD50 1715 mg/kg Acute Rat 2-Butoxyethanol (CAS 111-76-2) Acute Dermal LD50 Rabbit 400 mg/kg Acute Inhalation LC50 Mouse 700 ppm, 7 hours Inhalation LC50 Rat 450 ma/l. 4 hrs Acute Acute Oral LD50 Guinea pig 1.2 g/kg Acute Oral LD50 Mouse 1519 mg/kg Acute Oral LD50 Rabbit 0.32 g/kg 560 mg/kg Acute Oral LD50 Rat

Skin corrosion/irritation Causes skin burns.

Serious eye damage/ eye irritation Causes serious eye damage.

Not classified. Respiratory sensitization Not classified. Skin sensitization Germ cell mutagenicity Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Comment Component Result

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to

carcinogenicity to humans.

Not classified. Reproductive toxicity

Specific target organ toxicity -

single exposure

Irritating to respiratory system.

Specific target organ toxicity -

Not classified.

repeated exposure **Aspiration hazard**

Not classified.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is **Chronic effects**

repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects

have not been observed in humans.

Conforms to OSHA HazCom 2012 Standard

Section 12 - Ecological Information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not

exclude the possibility that large or frequent spills can have a harmful or damaging

effect on the environment.

Persistence and degradability The product is expected to be biodegradable.

Bioaccumulative potential Not known.

Partition coefficient n-octanol / water log (Kow)

Components Results
2-Butoxyethanol (CAS 111-76-2) 0.83
2-Amino Ethanol (CAS 141-43-5) -1.31

Mobility in soil Not available.

Mobility in generalThe product is water soluble and may spread in water systems.

Other adverse effects None known.

Section 13 - Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Waste codes should be assigned by the user based on the application for which the

product was used.

Waste from residues / unused

products

Dispose in accordance with all applicable regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after

container is emptied.

Section 14 - Transport information

DOT Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

Transportation in bulk according to Annex II of MARPOL 73/78 and

IBC Code

This substance/mixture is not intended to be transported in bulk.

Conforms to OSHA HazCom 2012 Standard

Section 15 - Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export

Notification (40 CFR707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001Not on regulatory list.

CERCLA Hazardous Substance List (40 CFR 302.4

Components 2-Butoxyethanol (CAS 111-76-2)

Result LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard Hazard Yes Categories **Delayed Hazard** No

Fire Hazard Nο Pressure Hazard No Reactivity Hazard No

SARA 302 Extremely hazardous No

substance

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

CAS# Chemical name % by wt. 2-Butoxyethanol 111-76-2 25 - 45

Not regulated.

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section

112 Hazardous Air Pollutants

Clean Air Act (CAA) Section 112(r) Accidental Release

Prevention (40 CFR 68.130)

Safe Drinking Water Act (SDWA) Not regulated. **Food and Drug Administration** Not regulated.

(FDA)

US state regulations

Proposition 65

US.Massachusetts RTK -Components

Substance List 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)

US.New Jersey Worker and Components

Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)

2-Amino Ethanol (CAS 141-43-5)

US.Pennsylvania RTK -Components

Hazardous Substances 2-Butoxyethanol (CAS 111-76-2)

2-Amino Ethanol (CAS 141-43-5)

US.Rhode Island RTK Components

> 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)

US - California California Safe Drinking Water and Toxic Enforcement Act of 1986

> (Proposition 65): This material is not known to expose you to any chemicals currently listed as carcinogens or reproductive toxins.

Conforms to OSHA HazCom 2012 Standard

International Inve	ntories	
Country(s) or region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notifed Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Section 16 - Other information, including date of preparation or last version

Revision date 6/1/2023 Version # 03

HMIS Hazard Codes PPE A

Disclaimer

The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.

^{*}A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).