

# 24/7® **Extended Performance Floor Finish**

#### DESCRIPTION

24/7 is a new, highly advanced floor finish with superior "off-the-mop" initial gloss. This ultra-high solids formula provides exceptional film clarity, repels soil and scratches, and extends the time between stripping cycles from 18 to 36 months. A wet-look gloss floor finish incorporating proprietary polymer technology producing outstanding long-term clarity, excellent abrasion resistance and extended durability. Excellent scrub and re-coat performance easily extends the time between stripping cycles from 18 to 36 months.

## **PRODUCT FEATURES / BENEFITS**

- Easy to Apply / Dries quickly, levels beautifully, no re-coat attack
- Ultra-High Solids / Save time and labor with fewer coats
- Scuff, scratch and abrasion resistant / Minimizes maintenance requirements
- Repels Dirt / Stays clean, clear and bright longer

## DIRECTIONS FOR USE

Floor Preparation: Strip old finish and wax using SUPER-SONIC Intensive Speed Stripper following label directions. For baseboards and corners, use PIZZAZZ Baseboard Stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coats of 24/7 Extended Performance Floor Finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

Buffing and Burnishing: 24/7 Extended Maintenance Floor Finish is an ideal for use in no-buff or buffing programs using all speeds of buffing or burnishing machines. Prior to buffing or Highest "Off-The-Mop" Gloss / Floors look beautiful, right from the start

- Excellent Burnish Response / Easily maintain wet-look gloss for extended period of time.
- Exclusive Micro Molecular Technology/ Superior durability. extremely consistent surface excel at long term performance.

burnishing dust mop the floor surface using CONTROL Dust Mop Treatment. Buff or dry burnish using NCL Aqua Magic buffing pad. For spray buffing, mop-on or autoscubber restoring use POP & Shine Gloss Restorer.

Routine Maintenance: Dust mop using mop treated with CONTROL Dust Mop Treatment. Damp mop or clean with an automatic scrubber using ENHANCE Neutral Floor Cleaner following label directions.

Scrub and Re-coat: When routine maintenance and buffing/ burnishing no longer responds as needed, scrub and re-coat using QWIK-SCRUB Scrub and Re-coat Cleaner following label directions

## SPECIFICATIONS

Туре	Pure acrylic polymers
Non Volatile Solids (%)	25.5 ± 0.5
рН	8.2 ± 0.2
Coverage (sq.ft./gal)	
Drying Time (minutes)	30
% Styrene (Free Monomer)	0.0

Specific Gravity (g/cc)	1.03 ± 0.01
Color	White, opaque liquid
Odor	Typical acrylic
Powdering	None
Flash Point	None
Slip Resistant	Yes
Shelf Life1 year minimum in origina	I unopened container

## SAFETY INFORMATION


CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage. Use with adequate ventilation.

FIRST AID: For Eyes: Flush eyes with water for at least fifteen minutes. If irritation persists seek medical attention. For Skin: Wash thoroughly with soap and water. If irritation persists seek



SSIFIC Floor Coating and Finishing Material As to Slip Resistance Only 18FI

HMIS HAZARD CODE	
1	HEALTH
0	FLAMMABILITY
0	PHYSICAL HAZARD



causes irritation, move to fresh air. **KEEP FROM FREEZING** 

For Commercial and Industrial Use Only



401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail:info@nclonline.com