

MATERIAL SAFETY DATA SHEET
(SIMILAR TO OSHA FORM 174)

N.A. = Not Applicable
Not Est. = Not Established
Prop. = Proprietary

SECTION 1 - MANUFACTURER / DISTRIBUTOR INFORMATION

Product Name: 365 Floor Finish / Wax

Supplier's Name: JANILINK

Supplier's Address: 3545 McCall Place, Sté. D, Doraville, GA 30340

HMIS Hazard Code: Health: 1 Flammability: 0 Reactivity: 0 Other: 0

Chemical Family: Floor Finish

D.O.T. Shipping Name: N/A

Emergency Phone #: (770) 216-9977

Chemical Name: Acrylic Latex Blend

Formula: N.A. Blended Product

Hazard Class: N/A D.O.T. ID#: N/A

SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NUMBER	% Concentration Range	Hazard Ratings (TLV/PEL)
None			

SECTION 3 - PHYSICAL DATA

Boiling Point (°F): Above 200

Vapor Pressure: = To Water

Vapor Density: = To Water

Solubility in Water: Disperses

Appearance: White, Opaque Liquid

Odor: Characteristically Acrylic

Specific Gravity: 1.034

Evaporation Rate: = To Water

SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point (°F): None to boiling (TOC)

Flammable Limits: N/A

Unusual Fire & Explosion Hazards: Heated material may liberate toxic fumes. Wear self contained breathing apparatus.

SECTION 5 - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation: No Skin: Yes Ingestion: Yes Threshold Limit Value: Not Est.

Effects of Overexposure: May cause skin and eye irritation. May be harmful if swallowed. If ingested, may cause severe gastric distress and blockage.

Emergency & First Aid Procedures: For Eyes: Flush eyes with water for at least fifteen minutes. If irritation persists seek medical attention. For Skin: Wash thoroughly with soap and water. If irritation persists seek medical attention. If ingested: Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

Conditions Aggravated by Exposure: None

Listed Carcinogen, Mutagen, Teratogen (Ingredient, Source, Amount): None

SECTION 6 - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: None

Incompatibility: Avoid contact with strong acids and oxidizers

Hazardous Decomposition Products: Carbon Oxides and Acrylates

Hazardous Polymerization: Will not occur.

SECTION 7 - SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled: Recontainerize by mopping, wet vacuum, or using a suitable absorbent.

Waste Disposal Method: Follow local, state, and federal regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not required

Ventilation: Local

Protective Gloves: Not required

Eye Protection: Goggles or safety glasses with side shields

Other Protective Equipment: None

SECTION 9 - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store between 40°F and 120°F. Keep from freezing.

Other Precautions: Keep out of reach of children. For professional use only.

The information contained in this MSDS was obtained from current and reliable sources, however the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of this company, it is not responsible for loss, injury and expense arising out of the product's improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use or disposal of this product which may be covered by this MSDS. The user is responsible for full compliance.

Date Prepared - 01/07/08 By: G.C.