



# BARE BONES® Low Odor

## Low Odor All-Purpose Speed Stripper

### DESCRIPTION

BARE BONES® LOW ODOR is a superior floor stripping formula that can be used anywhere, anytime! Like the original BARE BONES that set the standard for performance and labor savings some 20 years ago, BARE BONES® LOW ODOR from NCL provides the same rapid penetration and complete removal of even heavily burnished floor finish in a low odor formula that can be used in hospitals, schools and universities and office buildings. NCL chemists have designed a wetting system that keeps BARE BONES® LOW ODOR working at maximum effectiveness, with powerful film removing action easily cuts through multiple layers of finish easily! BARE BONES® LOW ODOR is a must for all professional floor care systems.

### PRODUCT FEATURES / BENEFITS

- Low odor
- No scrubbing machine needed
- High use-dilution for greater economy
- Can be used in automatic scrubbers (low foaming)
- Cuts through multi-layers of finish easily.
- Superior wetting.

### DIRECTIONS FOR USE

Dilute **BARE BONES® Low Odor** following dilution recommendations below. Dilute using cold or mildly warm water only.

Light/Normal Buildup: 8 oz per gallon of water (1:16)

Heavy Buildup (Burnished): 20 oz per gallon of water (1:5)

**Mop/Wet Vacuum Stripping System:** Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above

procedure before re-application of recommended NCL Floor Finish.

**Floor Machine Stripping System:** Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

**Note:** As some asphalt tiles may be damaged by prolonged soaking in concentrated strippers, a spot test is recommended before general use.

### SPECIFICATIONS

Color ..... Clear  
Odor ..... Mild  
pH ..... 11.7 ± 0.3  
Flash Point ..... 183°F  
Upper Cloud Point ..... > 130°F  
Lower Cloud Point ..... < 33°F  
Viscosity (cps) ..... < 5  
Water Solubility ..... Complete

Finish Removal..... Excellent  
Damage to Resilient Tiles ..... Minimal  
Density (lbs/gal) ..... 8.15 ± 0.1  
Specific Gravity (g/cc)..... 0.98 ± 0.01  
Free Rinsing ..... Yes  
Low Foaming ..... Yes  
Shelf Life..... 1 year minimum in original unopened container

### SAFETY INFORMATION


**WARNING: CAUSES SKIN AND EYE IRRITATION. HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.**

Avoid contact with skin, eyes and clothing. Do not ingest. Avoid exposure to mists or vapors. Use only with adequate ventilation.

**FIRST AID: For Eyes:** Flush eyes with water for at least fifteen minutes. Seek medical attention. **For Skin:** Wash skin thoroughly with water and apply emollient creme. If irritation persists seek medical attention. Remove and wash contaminated

clothing prior to reuse. **If ingested:** Do not induce vomiting. Give milk, egg white, gelatin, or large quantities of water. Seek immediate medical attention. Never give anything by mouth to an unconscious person. **For inhalation:** Move to fresh air. Seek medical attention if symptoms persist.

FOR COMMERCIAL AND INDUSTRIAL USE ONLY. READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.



Stripper

HMIS HAZARD CODE	
2	HEALTH
2	FLAMMABILITY
0	PHYSICAL HAZARD

**NCL®** World Class Cleaning Solutions®  
401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
www.nclonline.com • e-mail:info@nclonline.com