



# BARE BONES®

## No-Rinse / No Scrub Liquifying Stripper

### DESCRIPTION

A 55% active speed stripper that easily cuts through multi-layers of burnished floor finish. This "true" no-rinse stripper does not contain potassium hydroxide or sodium hydroxide yet is the fastest working liquifier on the market. Low foaming, no scrub and no rinse features make this product a must for all professional floor care systems.

### PRODUCT FEATURES / BENEFITS

- Low foaming / Can be used through automatic scrubbers
- Contains no potassium or sodium hydroxide / Safe for personnel & flooring
- Requires no rinsing / Saves time by eliminating neutralizing and rinsing
- No scrubbing machine needed / Reduces equipment costs & can be used in hard to get to places
- 55% Active / High use dilution for greater economy

### DIRECTIONS FOR USE

For the rapid removal of all floor finishes and waxes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt, linoleum, and rubber tiles. Also ideal for finished non-resilients such as: terrazzo, marble, ceramic, quarry tile, ceramic, quarry tile, concrete, and poured epoxy flooring. Although excellent for any type of equipment, greatest savings are realized when using automatic scrubbing equipment.

Dilute **BARE BONES®** following dilution recommendations below. Dilute using cold or mildly warm water only.

Light/Normal Buildup: 8 oz per gallon of water (1:16)

Heavy Buildup (Burnished): 20 oz per gallon of water (1:5)

**Mop/Wet Vacuum Stripping System:** Apply liberally with a mop to an area small enough so as not to allow the product to

dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above procedure before re-application of recommended NCL Floor Finish.

**Floor Machine Stripping System:** Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

**Note:** As some asphalt tiles may be damaged by prolonged soaking in concentrated strippers, a spot test is recommended before general use.

### SPECIFICATIONS

Color ..... Clear  
Odor ..... Sassafras  
pH ..... 11.8 ± 0.3  
Flash Point ..... None to Boiling  
Upper Cloud Point ..... > 130°F  
Lower Cloud Point ..... < 33°F  
Viscosity (cps) ..... < 5  
Water Solubility ..... Complete

Finish Removal..... Excellent  
Damage to Resilient Tiles ..... Minimal  
Density (lbs/gal) ..... 8.10 ± 0.1  
Specific Gravity (g/cc)..... 0.97  
Free Rinsing ..... Yes  
Low Foaming ..... Yes  
Shelf Life..... 1 year minimum in original unopened container

### SAFETY INFORMATION

**WARNING: CAUSES SKIN AND EYE IRRITATION. HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.**

Avoid contact with skin, eyes and clothing. Do not ingest. Avoid exposure to mists or vapors. Use only with adequate ventilation.

**FIRST AID: For Eyes:** Flush eyes with water for at least fifteen minutes. Seek medical attention. **For Skin:** Wash skin thoroughly with water and apply emollient creme. If irritation persists seek medical attention. Remove and wash contaminated

clothing prior to reuse. **If ingested:** Do not induce vomiting. Give milk, egg white, gelatin, or large quantities of water. Seek immediate medical attention. Never give anything by mouth to an unconscious person. **For inhalation:** Move to fresh air. Seek medical attention if symptoms persist.

FOR COMMERCIAL AND INDUSTRIAL USE ONLY. READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.



Stripper

HMIS HAZARD CODE	
2	HEALTH
2	FLAMMABILITY
0	PHYSICAL HAZARD



World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
www.nclonline.com • e-mail:info@nclonline.com