



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY 17SU

Maintenance Solutions

Granic Hard Surface Seal/Finish



Quarry Tile Brick

For Use On:

Slate Clay Tile

DESCRIPTION

An extremely durable, long lasting sealer/finish designed especially for terrazzo, quarry tile, brick, stone, Mexican tile, and all other non-resilient floors. Levels and adheres on all the above mentioned surfaces, leaving a durable high quality protective coating that lasts longer than most floor finishes found today.

DIRECTIONS

SEALING and FINISHING: Apply a liberal coat of sealer/finish evenly with a clean mop. Allow to dry for at least 30 minutes before applying additional coats. Two or three coats may be desired initially depending on the gloss desired and the condition of the floor.

MAINTENANCE: Use a treated dust mop for the removal of surface dirt and grit. Mop or scrub with a neutral or all-purpose cleaner to remove all soil. After cleaning touch up traffic lanes as necessary or recoat the entire floor. If spray buffing is desired, dust mop floor thoroughly and buff using a spray buff or polishing pad.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

PRODUCT SPECIFICATIONS

Type: Non-volatile solids: Color: Odor: pH: Dry/Recoat Time: Slip Resistance: Gloss: Leveling: Sediment:

Acrylic $18.0\pm0.5\%$ Milky white Mild 8.5 - 9.0 30 minutes .56 - .60 (ASTM-D2047-82)Greater than 88 Excellent 0.1% by volume, max. Removability: Detergent Resistance: Stain Resistance: Chemical Resistance: VOC Content: Storage/Stability: Freeze/Thaw Stability: Weight per Gallon: Coverage: With conventional strippers Excellent Very good Good 0.369 lbs./gal. 2 years Keep from freezing 8.57 lbs./gal. 1000-1500 ft² per gal. 1500-2000 ft² per gal.

Misco Products Corporation, Reading, PA (800) 548-4568 FAX (610) 926-1194 www.miscoprod.com an amanu a propusar

MATERIAL SAFETY DATA SHEET

IDENTIFICATION AND GUIDDI IED INFODMATION

(Prepared According to 29 CFR 1910.1200)

N/A=Not Applicable Effective Date: 1/09 Revision: n/a

SECTION I-PRU	DUCI IDENTIFICAT	ION	AND SUPPL	JEK I	NFUKMATIUN					
Manufacturer's Name:	Product Name: Granite				Supplier's Name:					
Misco Products Corporation	Generic Name: Hard Surf									
Manufacturer's Address:	Chemical Family: Acrylic Polymer Blend				Supplier's Address:					
1048 Stinson Drive Reading, PA 19605 Manufacturer's Phone #: (610) 926-4106	Formula: Proprietary				Supplier's Phone #					
					Supplier's Phone #	•				
SECTION 2-INGREDIENT INFORMATION										
CHEMICAL NAME	CAS NO.	WT.		PEL	TWA	-TLV	STEL-TLV			
Water	7732-18-5	to 100								
Acrylic Copolymer Dispersion Ethylene Copolymer	63744-68-3 9010-77-9	35 to 0 to 5								
Resin Solution	65405-63-2	0 to 5								
Diethylene Glycol Ethyl Ether	111-90-0	0 to 5								
	/ • •									
SECTION 3-PHYSICAL DATA			SECTION 4-FIRE AND EXPLOSION HAZARD DATA							
Boiling Point (°F): 212 F. Specific Gravity: 1.029			Flash Point (Method Used): N/A							
Vapor Pressure: 20mm Hg @ 68 F. Vapor Densi				Upper Explosion Limit: N/A Lower Explosion Limit: N/A						
% Volatile: 80+ pH: 8.5-9.0			Extinguishing Media: N/A							
	n Rate (Water=1): <1	Special Firefighting Procedures: Non Flammable								
Physical Description: Thin milky liquid with characteristic odor. Unusual Fire and Explosion Hazards: N/A										
SECTION 5-REACTIVITY DATA										
Stability: Stable			Hazardous Polymerization: None							
Hazards Decomposition Products: Will not occur.	Incompatibility (Materials to Avoid): None									
SECTION 6-STORAGE AND HANDLING INFORMATION Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For										
institutional and industrial use only. Avoid contact with a							uring storage. Fo	л		
SECTION 7-HEALTH HAZARDS AND FIRST AID			SECTION 8-SPECIAL PROTECTION INFORMATION							
Effects of Overexposure:			Respiratory Protection: Use in well-ventilated areas.							
Skin: Prolonged or repeated contact may cause dermatitis.			Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 in-							
Eyes: Eye irritant. May cause redness or swelling.			gredients below acceptable limit.							
Inhalation: Vapors may irritate nose, throat and lungs. May cause dizziness,			Protective Gloves: Chemical resistant rubber or neoprene.							
headache, nausea.			Eye Protection: N/A							
Ingestion: May be irritating to the mouth, throat, and gastrointestinal system.			Other Protective Equipment: Eyewash should be available nearby. Chemical							
Vomiting and diarrhea expected with large doses.			resistant footwear (rubber boots) when using product.							
First Aid Procedures:			SECTION 9-SPILL OR LEAK PROCEDURES							
Skin: Flush with water. Seek medical attention if irritation persists.			Steps to be taken in Case Material is Released or Spilled: Floors will become							
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical			slippery. Avoid walking in product. Keep unessential personnel away. Mop up or							
attention.			otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.							
Inhalation: Remove victim to fresh air. Seek medical attention if symptoms persist.			Waste Disposal Method: Any method in accordance with local, state and federal							
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.			laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream,							
рстыя.			river or to ground. Rinse container thoroughly before discarding in trash.							
	SECTION 10-REGULA		÷		· ·		6			
SARA Title III - Section 311/312 -Hazard Categ						HMIS Haza	rdous Materials			
No - Fire Hazard	FOR CONTAIN			leaning	Compound	Identificatio	n System			
No - Sudden Release of Pressure Hazard				-	-	Health		1		
No - Reactivity Hazard	FOR 1 GALLO	N CON	TAINERS : C	leaning	Compound	Flammabilit	v	0		
Yes - Immediate (acute) Health Hazard				0	1	Reactivity		0		
No - Delayed (chronic) Health Hazard	FOR CONTAIN	VERS <	1 GALLON :	Cleanir	ng Compound	Personal Pro	otection	A		
FOR EMERGENCY MEDICAL OR TRANSPORT IN	FORMATION: CHEM-TI	EL, Inc	. @ 800-255-3	924	(24 hours, 7 days pe	r week)				
This product contains the following toxic chemical(s) subje	act to the reporting requirem	onte of	section 212 of	the Em	arganov Dianning an	d Community D	ight To Know A	ct		
of 1986 and of 40 CFR 372.	set to the reporting requirem	ients of	section 313 OI	ine Em	lergency Flanning and	a Community R	ight-10-Know A	υl		
CAS# Chemical Name			Percent by Weight							
	None					0				

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.
CAS#
Chemical Name
Percent by Weight
None

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product