Manufacturer's Name:

MATERIAL SAFETY DATA SHEET

N/A= Not Applicable Prepared by: Regulatory Affairs Dept. (Prepared According to 29 CFR 1910.1200) Effective Date: 10/13 Revision: N/A

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Misco Products Corporation Generic Name: Ultra Compatible Floor Finish Manufacturer's Address:

Supplier's Address: Chemical Family: Acrylic Wax Blend 1048 Stinson Drive Reading, PA 19605 Formula: Proprietary Manufacturer's Phone #: (610) 926-4106 Supplier's Phone #:

Product Name: eLuminate

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Zinc-Free Acrylic Copolymer Dispersion	N/A	45 to 50			
Modified Propylene Copolymer	25722-45-6	0 to 5			
Oxidized Polyethylene	68441-17-8	0 to 5			
Tributoxyethyl Phosphate	78-51-3	0 to 5			
Diethylene Glycol Ethyl Ether	111-90-0	0 to 5			
TXIB TM Formula Additive	6846-50-0	0 to 5			

SECTION 3-PHYSICAL DATA SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Specific Gravity: 1.015 – 1.025 Flash Point (Method Used): None (water based) Boiling Point (°F): 212 F.

Upper Explosion Limit: N/A Lower Explosion Limit: N/A Vapor Pressure: <20mm Hg @ 68 F. Vapor Density (Air=1): =1 Extinguishing Media: N/A % Volatile: 75+ **pH:** 7.3 - 8.5

Special Firefighting Procedures: Non Flammable Solubility in Water: Complete **Evaporation Rate (Water=1):** <1 Unusual Fire and Explosion Hazards: N/A

Physical Description: Thin milky liquid with characteristic odor. VOC Content (% wt.): None

SECTION 5-REACTIVITY DATA Hazardous Polymerization: None Stability: Stable Hazards Decomposition Products: Will not occur Incompatibility (Materials to Avoid): None SECTION 6-STORAGE AND HANDLING INFORMATION

CAUTION. Moderate eye irritant. Avoid contact with eyes, skin and clothing. Avoid breathing of vapors. Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:

Skin: Prolonged or repeated contact may cause dermatitis.

Eyes: Eye irritant. May cause redness or swelling.

Inhalation: Prolonged exposure may cause dizziness, headache, nausea. **Ingestion:** May be irritating to the mouth, throat, and gastrointestinal system.

Vomiting and diarrhea expected with large doses.

First Aid Procedures:

Skin: Flush with water. Seek medical attention if irritation persists.

Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.

Inhalation: Remove victim to fresh air and monitor. Seek medical attention if symptoms persist.

Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated areas only.

Ventilation Requirements: Provide local exhaust to keep TLV of Section 2

Supplier's Name:

ingredients below acceptable limit.

Protective Gloves: Rubber or chemical resistant. Eye Protection: Safety glasses or chemical splash goggles

Other Protective Equipment: Chemical resistant footwear e.g. rubber boots to

protect feet. Long pants to protect legs.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.

Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before offering for recycling.

0

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories: **Shipping Information: HMIS Hazardous Materials**

Identification System No - Fire Hazard FOR CONTAINERS > 1 Gallon: Liquid Floor Wax

Health No - Sudden Release of Pressure Hazard

Flammability No - Reactivity Hazard FOR 1 GALLON CONTAINERS: Liquid Floor Wax Yes - Immediate (acute) Health Hazard Reactivity No - Delayed (chronic) Health Hazard FOR CONTAINERS < 1 GALLON: Liquid Floor Wax **Personal Protection**

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS# Chemical Name Percent by Weight

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

None

CAS# **Chemical Name** Percent by Weight

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product