

# **Chemical Specialties Manufacturing Corporation**

901 N. Newkirk Street / Baltimore, MD 21205 / (800) 638-7370

# MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Degree of hazard: 4 = Extreme, 3 = High, 2 = Moderate, 1 = Slight, 0 = Insignificant

Health: 1 Flammability: 2 Reactivity: 0

## **SECTION I: PRODUCT IDENTIFICATION**

PRODUCT NAME: Professional Spot Lifter DATE REVIEWED: July 9, 2009

N/D = Not determined.

DOC CODE: W.20392 CHEMICAL FAMILY: Mixture

EMERGENCY 24-HOUR TELEPHONE # 1-800-424-9300 (CHEMTREC)

N/A = Not applicable or Not available.

# **SECTION II: COMPOSITION/INFORMATION ON INGREDIENTS**

This product has not been tested as a whole for health effects on animals or humans. According to the OSHA Hazardous Communications Standard (29 CFR 1910.1200) any hazardous ingredients that comprise >1.0% of the material and any carcinogenic ingredients that comprise >0.1% must be listed on the MSDS. When individually tested at 100% ingredients in the make-up of this product posed the following health hazards.

#### **SECTION II a: HAZARDOUS INGREDIENTS >1.0%**

Chemical Name	CAS#	OSHA PEL	ACGIH TLV	Percentage
2-Butoxyethanol	111-76-2	50 ppm	20 ppm	5-10%
Odorless Mineral Spirits	8052-41-3	500 ppm	100 ppm	1-5%
Sodium Olefin Sulfonate	68439-57-6	N/A	N/A	1-5%
D-Limonene	5989-27-5	N/A	N/A	1-5%

## **SECTION II b: CARCINOGENIC INGREDIENTS AT >0.1%**

None.

#### **SECTION III: HAZARDS IDENTIFICATION**

EYES: May cause eye irritation.

SKIN: None expected if used as directed. INHALATION: None expected if used as directed.

INGESTION: May cause abdominal discomfort, nausea and diarrhea.

#### **SECTION IV: FIRST AID PROCEDURES**

EYES: Remove contacts. Flush with water for at least 15 minutes. If irritation persists consult physician.

INGESTION: Drink 1 to 2 glasses of water. If discomfort persists, consult physician.

INHALED: Remove to fresh air. If symptoms persist or are severe seek prompt medical assistance. SKIN: Remove contaminated clothing. Thoroughly wash exposed area with soap and water.

PHYSICIAN: Treatment based on judgment of attending physician.

## **SECTION V: FIRE AND EXPLOSION DATA**

FLASH POINT: 118°F (47.8°C)

AUTO-IGNITION TEMPERATÚRE: N/D EXPLOSIVE LIMITS - UEL: N/D LEL: N/D

EXTINGUISHING MEDIA: Any standard extinguishing media (alcohol foam, water spray or fog, CO<sub>2</sub> dry chemical, etc.). SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH/MSHA approved self-contained positive pressure breathing

apparatus and protective clothing where this material is involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

#### **SECTION VI: ACCIDENTAL RELEASE MEASURES**

Soak up spilled material with absorbent material. Scoop or sweep and dispose according to local, state and federal regulations.

#### **SECTION VII: HANDLING AND STORAGE**

Avoid heat, flame, and sparks. Keep container closed to avoid contamination.

#### **SECTION VIII: PROTECTION MEASURES**

VENTILATION: Local exhaust or dilution ventilation is necessary in poorly ventilated areas.

GLOVES: Chemical resistant gloves.

RESPIRATORY: When mists or aerosols are anticipated, wear NIOSH/MSHA approved respirator equipped with organic vapor cartridges with high-efficiency particulate filters.

EYE: Safety glasses. Wear splash goggles when mists or aerosols are anticipated.

OTHER PROTECTIVE EQUIPMENT: Body-covering clothing should be worn.

## **SECTION IX: PHYSICAL/CHEMICAL DATA**

APPEARANCE AND ODOR: Opaque white liquid with citrus odor. WATER SOLUBILITY, % BY WT: N/D

% VOLATILE BY WT.: ~14% pH: 8.4 – 9.4

SPECIFIC GRAVITY: 0.989 g/cc WT/GAL: 8.24 lbs/gal

# **SECTION X: REACTIVITY DATA**

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur. INCOMPATIBILITY: Strong oxidizers and strong acids.

HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS: Oxides of carbon, sodium, sulfur and possibly other

unidentified organic compounds.

# **SECTION XI: TOXICOLOGICAL INFORMATION OF INGREDIENTS**

2-Butoxyethanol: LD50 oral rat: 470-3000 mg/kg. LD50 dermal rabbit: 99-610 mg/kg. Odorless Mineral Spirits: LD50 oral rat: >5000 mg/kg. LD50 dermal rabbit: >3000 mg/kg.

Sodium Olefin Sulfonate: LD50 oral rat: 500-5000 mg/kg. LD50 dermal rabbit: 400-2000 mg/kg.

D-Limonene: LD50 oral rat: 5000 mg/kg. LD50 dermal rabbit: >5000 mg/kg.

## **SECTION XII: ECOLOGICAL INFORMATION**

Product may not be completely biodegradable.

2-Butoxyethanol: LC50 rainbow trout (96hr): 1700 mg/L. LC50 daphnia magna: 835 mg/L. EC50 daphnia magna: 1600-2500

mg/L. LC50 grass shrimp (96hr): 5.4 mg/L. LC50 shrimp (96hr): 550-950 mg/L.

Sodium Olefin Sulfonate: LC50 fish: 1-10 mg/L.

## **SECTION XIII: SPILL, LEAK AND DISPOSAL PROCEDURES**

WASTE DISPOSAL: In accordance with Federal, state and local regulations.

NEUTRALIZING CHEMICALS: Water.

#### **SECTION XIV: TRANSPORT INFORMATION PER 49 CFR 172.101**

All ingredients used in this formula are non-regulated for non-bulk.

#### **SECTION XV: REGULATORY INFORMATION**

Domestic	International:	
TSCA: All ingredients are listed on the TSCA chemical	European labeling requirements:	
substance inventory.	Symbol: Xi: Irritant. F: Flammable	
SARA Section 313 Ingredients: 2-Butoxyethanol.	R-Sentences: R10, R36, R38	
California Prop 65 Ingredients: None.	S-Sentences: S2, S24, S25, S37, S39	
	Canadian: WHMIS Hazard Class: D2B. B2	

## **SECTION XVI: OTHER INFORMATION**

One should always use chemicals with awareness of potential hazards, known and unknown, and their effect on the human system. We urge users to minimize employee exposure to all chemicals, including this product and to keep the level of exposure commensurate with good industrial hygiene practices.

# **DISCLAIMER OF LIABILITY**

The manufacturer and seller warrants that this product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.