**UP TO 3000 PSI** 

**UP TO 4.0 GPM** 



## 고압세척기 pw02-1

**BLACK & RED POWDER COATED FRAMES** 

**PACKAGING: Boxed** 



#	Model#		Engine	Pump	PSI	GPM	Weight
53	PE-2030EW1COM		3.0 HP (1 phase) 220V	Comet LWD-K2020	2,000	2.2	135 lbs
54	PE-2050EW1COM		5.0 HP (1 phase) 220V	Comet FWS3530E	2,000	3.5	200 lbs
55	PE-2050EW3COM		5.0 HP (3 phase) 575V	Comet FWS3530E	2,000	3.5	200 lbs
56	PE-2775EW1COM	<b>MODEL SHOWN</b>	7.5 HP (1 phase) 220V	Comet FWS3530E	2,700	3.5	230 lbs
57	PE-2775EW3COM		7.5 HP (3 phase) 575V	Comet FWS3530E	2,700	3.5	230 lbs
58	PE-3010EW3COM		10 HP (3 phase) 575V	Comet FWS4030E	3,000	4.0	230 lbs
59	PE-2050EW3COM4		5.0 HP (3 phase) 460V	Comet FWS3530E	2,000	3.5	200 lbs
60	PE-2775EW3COM4		7.5 HP (3 phase) 460V	Comet FWS3530E	2,700	3.5	230 lbs
61	PE-3010EW3COM4		10 HP (3 phase) 460V	Comet FWS4030E	3,000	4.0	230 lbs

Pic	Feature	Pic	Feature	Pic	Feature
•	4,400 - 12,000 Cleaning Units	4	50' Steel Braided Rubber Hose	•	Black/Red Powder Coated Frame
•	Baldor Electric Motor	5	5,000 PSI Spray Gun	•	Direct Drive
1	Thermal Relief Valve (145°)	6	36" Insulated Lance	•	Box Dimensions: H25", L31", W24"
2	2 13"Tubed Pneumatic Tires		4 Quick-Connect Spray Tips		
3	Chemical Injector Kit	•	Does not include Cord, Switch or Plug		
1 2 3	13"Tubed Pneumatic Tires 7 4 Quick-Connect Spray Tips		4 Quick-Connect Spray Tips	•	Box Dimensions: H25", L31", W24"



















4000 PSI

8.0 GPM



## 고압세척기 pw02-2

24" WHIRL-A-WAY, STAINLESS STEEL

**PACKAGING: Boxed** 

## STAINLESS STEEL O



Circular design allows a zero wall clearance.



Sample look at the cleaning results of a Whirl-A-Way.



The following comparison chart shows the time taken to clean a typical size driveway (400 sq. ft.) using 3 different components.

	Unit	Time to clean		
▶	Whirl-A-Way	10 Minutes		
	<b>Water Broom</b>	30 Minutes		
	Spray Nozzle	80 Minutes		

## Whirl-A-Way Rotary Head Breakdown



<b>85.300.044</b> Ball Valve Kit	

Allows you to switch between Whirl-A-Way and Wand without having to shutdown the unit.



Part#	Replacement Part
85.790.004	Rotary Head
85.791.010S	Tri-Rotary Arm 11"r
85.790.020	1½ Caster
85.790.010	Rotary Head Repair Kit
85.225.020	Replacement Nozzle Tip
85.790.0195	Nylon Bursh Skirt

#	Model#		Max Pressure	Max Flow	Max Temp.	Size	Weight
1	BE-2400WAWS	<b>MODEL SHOWN</b>	4,000 PSI	8.0 GPM	160°F	24" diameter	45 lbs.

Pic	Feature	Pic	Feature
1	Non Marking Casters	5	Welded Elbows and Assembly
2	Stainless Steel Housing/Bearings on Casters	6	Field Repairable Gun
3	4,000 PSI Head, 160°F	•	Water Flow Out Front Preventing Cavitation
4	Welded Stainless Steel Rotary Arm	•	Zero Wall Clearance













